



## ACOUSTICAL SEALANT

### DESCRIPTION

OSI® SC-175 Acoustical Sealant is a non-flammable, latex-based sealant specially designed to reduce sound transmission and drafts in all types of wall systems where a sound-rated assembly is required. Its primary function is to achieve and maintain the specific STC (Sound Transmission Class) value of the system designed.

The paintable sealant remains flexible and adheres firmly to wood, metal studs, concrete, gypsum board and most other building materials. The easy-to-use sealant cleans up easily with soap and water.



### TECHNICAL CHARACTERISTICS

Size	29 oz
Color	White

### FEATURES

- Permanently Flexible
- Easy Application and Cleanup
- UL Classification - R9732; UL 723
- Low VOC Compliant Formula
- Non-Staining & Non-Migrating
- High Degree of Adhesive and Cohesive Strength
- Non Flammable
- Cure Time 2-7 Days
- Application Temperatures 40 ° F Minimum
- Service Temperature -5° F - 170° F
- Freeze-Thaw Stability 3 Cycles. Unaffected by Freezing After Curing
- Shelf Life 1 Year from Date Made at 75° F
- Can be Applied to Drywall, Concrete, Plaster, Steel, Wood and Aluminum Surfaces without Priming

### APPLICATIONS

- Multi-Family
- Commercial
- Hotel Rooms
- Conference Rooms
- Home Theaters

