



ALPHAENVIRO ACOUSTIC CEILING TILES



DESCRIPTION

AlphaEnviro Acoustic Ceiling Tiles are very popular ceiling tiles in theaters, music studios, and home theaters.

The AlphaEnviro Acoustic Ceiling Tiles come in standard sizes of 2' x 2' and 2' x 4' and standard thicknesses of 1" and 2" and easily install into any standard suspended ceiling grid system. The ceiling tiles are either PVC faced or PVC encapsulated.

The ceiling tiles offer high sound absorption ratings, NRC .80 – 1.15.



SOUND ABSORBING PERFORMANCE

	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC*
1" Thick	.14	.27	.80	1.11	1.14	1.14	.85
2" Thick	.22	.81	1.24	1.30	1.21	1.16	1.15

*Noise Reduction Coefficient

TECHNICAL CHARACTERISTICS

Size	2' x 2', 2' x 4'
Thickness	1", 2"
Colors	Many; See Color Chart
Density	6 lb pcf
Finishes	PVC Cloth

FEATURES

- Flexible & lightweight for easy installation
- Class 1 Fire Rated
- Easily cleanable finish

COMMON APPLICATIONS

- Commercial Spaces
- Industrial and Manufacturing
- Schools and Universities

