

## ALPHAENVIRO PVC/RIPSTOP ACOUSTIC PANELS



### DESCRIPTION

AlphaEnviro Acoustic Panels are a sound absorbing acoustical treatment with a washable surface. They are available in two thicknesses and densities and in two coverings: PVC and Ripstop Nylon.

PVC combines strong sound absorption with a washable surface. Ripstop Nylon coverings offer an extremely durable panel that can withstand high abuse.

These acoustic panels are excellent for treating large open rooms and work well to reduce reverberation and increase speech intelligibility.



### SOUND ABSORBING PERFORMANCE

	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC*
1" Thick	.08	.24	.62	.92	1.07	1.05	<b>.70</b>
2" Thick	.27	.65	1.06	1.16	1.14	1.12	<b>1.00</b>

\*Noise Reduction Coefficient

### TECHNICAL CHARACTERISTICS

Size	Custom up to 4' x 10'
Thickness	1", 2"
Colors	Many; See Color Chart

### FEATURES

- Class 1 Fire Rated
- Options for grommeting
- 1.65—3 lb psf density

### APPLICATIONS

- Gymsnasiums
- Multipurpose Rooms
- Animal Shelters & Hospitals
- Industrial Facilities
- Manufacturing Plants
- Auditoriums
- Restaurants
- Telecommunication Centers

