



## SIGNATURE ACOUSTIC CEILING TILES



### DESCRIPTION

Signature Acoustic Ceiling Tiles are excellent for lowering reverberation (echo) levels in rooms.

The acoustic tile consists of a 1" thick, 6 pound density fiberglass board covered with your choice of four facings; white pebble grain vinyl, white nubby cloth, or black felt.

These fiberglass tiles are an excellent sound absorber with a NRC rating of .85 and are Class 1 Fire Rated. The Signature Acoustic Ceiling Tiles come in standard sizes of 2' x 2' and 2' x 4' and standard thickness of 1".



### TECHNICAL CHARACTERISTICS

Size	2' x 2', 2' x 4'
Thickness	1"
Finishes	White Pebble Grain Vinyl, White Nubby Cloth, Black Felt
Density	6 lbs pcf

### SOUND ABSORBING PERFORMANCE

125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC*
.14	.27	.80	1.11	1.14	1.14	.85

\*Noise Reduction Coefficient

### FEATURES

- Lightweight for easy drop system installation
- Class 1 Fire Rated
- Fits into 2' x 4' or 2' x 2' drop ceiling grids
- Four facing options

### COMMON APPLICATIONS

- Commercial Spaces
- Cinemas and Home Theaters
- Production Studios
- Schools and Universities
- Government Facilities
- Houses of Worship
- Restaurants and Hospitality



White Pebble Grain Vinyl

White Nubby Cloth

