

For every environment of your life.

2420 Grenoble Road Richmond, VA 23294

Toll Free: 800-782-5742











Guilford of Maine Lido Fabric



DESCRIPTION

Our Guilford of Maine Lido Acoustic Fabric is used to wrap an acoustical substrate or other absorptive material. The Lido series combines multiple thread colors to produce a textured finish, allowing you to match or compliment a range of design options. The designer fabric's texture provides a clean and beautiful finish for your project.

FEATURES

- Acoustical panel fabric
- Cleanable with water based cleaning agents

TECHNICAL CHARACTERISTICS

SIZE: 66" wide x 36" yard

MATERIALS: 52% Post-consumer polyester

48% Post-consumer polyester

Weight: 11.5 +/- 0.5 oz./ linear yard

Repeat: None

Fire Rating: Class 1 or A per ASTM E84

Breaking Strength: 100 lbf min. warp and fill

and 125 lbf min fill (ASTM D5034)

Colorfastness to light (AATCC 16 Option 3): Grade 4 min at 40 hours

Colorfastness to crocking (AATCC 8): Grade 4 min. dry & Grade 3 min. wet

Colors may vary between dye lots.

The plot below summarizes impedance tube measurements of absorption of an anechoic termination and various fabrics in front of the anechoic termination.

Acoustical Performance for Panel Applications (ISO 10534-2)



