

Technical Data Sheet

AcousticalSolutions.com 800-782-5742









ISO-STEP FLOOR UNDERLAYMENT



DESCRIPTION

Iso-Step Floor Underlayment is an environmentally friendly rubber based product made from recycled tires that is available in 1 pound per square foot and 2 pound per square foot models. It offers credible sound reduction of both airborne and structure borne noise.

Iso-Step Floor Underlayment also offers STC performance superior to other underlayments in the market today. The 1/4" thick model has an STC 26, and the ½" thick model has an STC 31.

Iso-Step can be installed over wood or concrete subfloor and can be installed beneath hardwood, vinyl, tile and carpet flooring. Iso-Step Floor Underlayment is economically priced and ships quickly.

TECHNICAL CHARACTERISTICS

Size 4' x 25' rolls

1/2", 1/4" **Thickness**

Color Black

SOUND BLOCKING PERFORMANCE

	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	STC*
¼" Thick	13	17	22	26	32	37	26
½" Thick	16	22	26	32	35	40	31

^{*}Sound Transmission Class

FEATURES

- Easily installed
- **Excellent STC ratings**
- Can be used with a variety of subfloor and flooring substrates

COMMON APPLICATIONS

- Residential
- Commercial
- **Public Facilities**





