

Green Glue Noiseproofing Joist Tape

PREPARE FOR APPLICATION

The Green Glue Noiseproofing Joist Tape is 100 linear feet long and available in widths of 1-7/16", 2-1/4", and 3". Select the width appropriate for your floor joists. Make sure all surfaces are free from dirt, ice, and water before applying the Noiseproofing Joist Tape.

INSTALLING GREEN GLUE NOISEPROOFING JOIST TAPE

Apply the Noiseproofing Joist Tape adhesive side down evenly to the top of each floor joist. Once placement of the Noiseproofing Joist Tape is complete, apply the subfloor as normal to joists. **Please note:** The use of construction adhesive is NOT recommended when securing the subfloor and will compromise the effectiveness of the Noiseproofing Joist Tape.



Please Note: These installation instructions are given as a general guide to avoid common errors. Installer should follow best practices for construction and workmanship. Acoustical Solutions bears no responsibility for installation or contractor selection. Please contact a sales representative if you have questions, concerns or specific project requirements.

Be sure to inspect materials upon delivery. Please note any damage on the delivery ticket and notify Acoustical Solutions immediately. Materials should be stored in original packing in a clean, climate controlled environment free of moisture. Installation should not commence until building is enclosed and under standard occupancy conditions and surfaces are of clean, acceptable condition and properly prepared. Installation is best done at the end of a construction project. Do not install materials of unacceptable quality.

