

## SONEX<sup>®</sup> ACOUSTIC PANEL ADHESIVE DATA SHEET



### TECHNICAL CHARACTERISTICS

**SIZE:** 10.5 fl. oz. tube

**COVERAGE:** Approximately 16–24 square feet per tube

**STORAGE:** PROTECT FROM FREEZING.  
Store in a cool, dry place at room temperature. For maximum shelf life store at 75°F (24°C).

**DISPOSAL:** Take unwanted product to an approved household hazardous waste transfer facility. Hardened material may be disposed of with trash.



### DESCRIPTION

The Sonex<sup>®</sup> Acoustic Panel Adhesive has been specially formulated for use with our Sonex<sup>®</sup> acoustic foam panels. One 10.5 ounce tube installs approximately 16–24 square feet of Sonex<sup>®</sup> acoustic foam wall panels and fits into a standard caulking gun.

This non-toxic, water-based adhesive makes installation hassle-free and provides a strong, permanent bond when adhering Sonex<sup>®</sup> melamine materials to walls or ceilings. Compatible with Sonex<sup>®</sup> Panels in both polyurethane and Willtec<sup>®</sup> foams. Sonex<sup>®</sup> Acoustic Panel Adhesive provides easy clean-up with water.

### FEATURES

- Non-flammable
- Quick tack time
- Water-resistant
- Odorless
- Non-toxic

