

## SONEX<sup>®</sup> WHISPERWAVE SOUND BAFFLE DATA SHEET



### DESCRIPTION

Whisperwave<sup>®</sup> Sound Baffle curved accent products allow you to unleash your creativity while reducing noise and reverberation. Whisperwave Sound Baffles create movement and are easily hung using a wall-to-wall system.

Ride the wave with Whisperwave<sup>®</sup>. Made from Class 1 fire-rated melamine foam, Whisperwave<sup>®</sup> products are safe for use in a wide range of applications.

Whisperwave<sup>®</sup> products are lightweight and easy to install. Whisperwave<sup>®</sup> products are available in natural white, natural grey or HPC Coated coated colors.

### TECHNICAL CHARACTERISTICS

**SIZE:** 2' x 4'

**THICKNESS:** 2"

**MATERIALS:** Open-cell melamine foam core

**FIRE RATING:** Class 1 per ASTM E 84  
Meets UL 1715 (willtec natural)

**COLORS:** Natural White, Natural Grey, or HPC Coated Colors

**MOUNTING:** Corkscrew hangers (Sold Separately) are installed in the field for either wall-to-wall cable installation or ceilingmounted cable installation. Can be aligned in the same direction or arranged so that every other baffle is turned 90 degrees.

#### SOUND ABSORBING PERFORMANCE

*(Sabins per Baffle per ASTM C423-90a)*

Thickness	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	Ave.
2"	1.0	5.4	10.8	16.3	18.7	24.0	12.7

