

WhisperWave[®] Sound Baffle



DESCRIPTION

Whisperwave[®] Sound Baffle curved accent products allow you to unleash your creativity while reducing noise and reverberation. Whisperwave Sound Baffles create movement and are easily hung using a wall-to-wall system.

Ride the wave with Whisperwave[®]. Made from Class 1 fire-rated melamine foam, Whisperwave products are safe for use in a wide range of applications.

Whisperwave[®] products are lightweight and easy to install. Whisperwave[®] products are available in natural white, natural grey or HPC Coated coated colors.

TECHNICAL CHARACTERISTICS

SIZE: 4' x 2'

THICKNESS: 2"

MATERIALS: Open-cell melamine foam core

FIRE RESISTANCE: Class 1 per ASTM E 84
Meets UL 1715 (willtec natural)

COLORS: Natural White, Natural Grey or HPC Coated Colors

MOUNTING:

Corkscrew hangers (Sold Separately) are installed in the field for either wall-to-wall cable installation or ceiling-mounted cable installation. Can be aligned in the same direction or arranged so that every other baffle is turned 90 degrees.

SOUND ABSORPTION						
Sabins per 24" x 48" x 2" Baffle						
125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	Ave.
1.0	5.4	10.8	16.3	18.7	24.0	12.7

