

POLYWRAP SOUND BAFFLES



DESCRIPTION

Polywrap™ Sound Baffles are an economical and effective solution to industrial facility noise problems.

This lightweight baffle is made of a heat-sealed polyethylene bag encompassing a sound absorptive fiberglass board.

PolyWrap is available in two facing colors, is class 1 fire rated, and is manufactured with two grommets along one side for easy installation.



TECHNICAL CHARACTERISTICS

Size	4' x 2'
Thickness	1½"
Colors	White, Black
Weight	2lbs per baffle

FEATURES

- Class 1 Fire Rated
- 1.6 lb per cubic foot density core
- Lightweight
- Grommeted with options for custom placement

COMMON APPLICATIONS (upper case, 10pt. Calibri)

- Industrial Facilities
- Warehouses
- Indoor Pools
- Gymnasiums
- Auditoriums



SOUND ABSORBING PERFORMANCE

125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	Sabins*
2.1	6.5	10.7	14.1	12.7	8.1	11.0

*Average sabins per baffle

125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
0.26	0.81	1.33	1.76	1.58	1.01	1.35

