

ACOUSTILIGHT™ SURFACE MOUNT FIBER OPTIC CEILING TILES

ASI Surface Mount Panels are produced with 2" of premium 6 lb. Density acoustic fiberglass providing a greater than 1.0 noise reduction coefficient. Panels come with beveled edges for easier installation and a refined look. Each panel is wrapped in standard black or midnight blue fabric. The power requirement per panel is 12 volts DC and draws on 0.36 watts of power. If needed, optional BluRay lighting is driven of a separate source.



| | |
|-----------------------------|------------------------|
| Size | 48" x 48" x 2" |
| Color | Midnight Blue or Black |
| Star Color Temp | 6500 K |
| Number of Stars | 45 |
| Stars per sq. ft. | 2.82 |
| Weight | 16 lbs. |
| Power Requirement | 12v DC |
| Power Consumption | 0.36w |
| Fiber Glass | 6 lb. Density |
| Noise Reduction Coefficient | > 1.0 N.R.C. |
| Mounting | (4) Surface Anchors |

Each panels has an 8" No Cut Zone clearly marked on the back. All other brands or product names are trademarks or registered trademarks of their respective owners. Specifications are subject to change without notice. ASI strives to use only materials

that carry ASTM E 84 Class A or 1 fire rating. Low voltage lighting – not all materials carry an independent lab listing.