

ALPHAFLEX CEILING BANNERS



DESCRIPTION

AlphaFlex Ceiling Banners provide excellent sound absorption. They are especially effective and cost efficient for large, open facilities that require high levels of noise control. These banners are easily cleanable due to their PVC covering. AlphaFlex is designed to hang vertically from or parallel to the ceiling via grommets or wooden mounting stays.



PVC SOUND ABSORBING PERFORMANCE

	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC*
2" Thick	1.09	.97	.92	1.05	1.00	1.11	1.00
4" Thick	1.31	1.11	1.14	1.17	1.15	1.19	1.15

*Noise Reduction Coefficient

TECHNICAL CHARACTERISTICS

Size	Custom up to 4' x 20'
Thickness	2" or 4"
Colors	Many; See Color Chart

FEATURES

- Class 1 Fire Rated
- .75 lb per square foot density
- Easy to maintain

COMMON APPLICATIONS

- Gymsnasiums
- Multipurpose Rooms
- Hospitals
- Industrial & Manufacturing Plants
- Auditoriums Areas
- Restaurants & Night Clubs
- AV Production Rooms

RIPSTOP SOUND ABSORBING PERFORMANCE

	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC*
2" Thick	-	-	-	-	-	-	.90
4" Thick	-	-	-	-	-	-	1.00

*Noise Reduction Coefficient

