

## SONEX<sup>®</sup> Contour Panel



### DESCRIPTION

The Sonex<sup>®</sup> Contour Panel combines sound absorption with an eye-pleasing design for direct mount wall or ceiling applications.

With two available thicknesses, you can achieve the desired amount of absorption for your project. These are constructed a Class 1 fire rated acoustical foam that meets public building code requirements.

Sonex<sup>®</sup> Contour Panels easily adds sound absorption to any room, lowering reverberation and echo while improving speech intelligibility.

### TECHNICAL CHARACTERISTICS

<b>SIZE:</b>	24" x 24"
<b>THICKNESS:</b>	1", 1-3/4"
<b>MATERIAL:</b>	Open-cell melamine-based foam
<b>FINISH:</b>	HPC Coated
<b>COLOR:</b>	Arctic White
<b>PATTERN:</b>	Basix
<b>FIRE RESISTANCE:</b>	Class 1 per ASTM E 84
<b>NRC:</b>	0.65- 0.90

**MOUNTING:** Attach to wall and/or ceiling surface with a water-based construction adhesive.



### SOUND ABSORPTION

(Per ASTM C423-90; Mounting Type A)

Thickness	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
1"	0.12	0.24	0.59	0.89	0.96	0.99	0.65
1-3/4"	0.21	0.48	0.93	1.09	1.09	1.04	0.90

