

WhisperWave[®] Ribbon Sound Baffle



DESCRIPTION

The Whisperwave[®] Ribbon Sound Baffle allows you to unleash your creativity while reducing noise and reverberation. Add dimension and acoustical control right where you need it the most with Whisperwave[®] Ribbons. Suspend Whisperwave Ribbons from ceiling-mounted cables using corkscrew hangers (Sold Separately). They may be hung as high or as low as necessary to avoid obstacles in the ceiling, work around HVAC or to achieve a particular design.

Made from Class 1 fire-rated melamine foam, Whisperwave[®] products are offered in standard and custom sizes and curve patterns. Whisperwave[®] products are lightweight and easy to install. Whisperwave[®] products are available in natural grey, natural white or may be HPC Coated to add color and additional protection.

TECHNICAL CHARACTERISTICS

SIZE: 4' x 1'

THICKNESS: 2"

MATERIALS: Open-cell melamine foam core

FIRE RESISTANCE: Class 1 per ASTM E 84
Meets UL 1715 (willtec natural)

COLORS: Natural White, Natural Grey or HPC Coated Colors

MOUNTING:

Corkscrew hangers (Sold Separately) are installed in the field for either wall-to-wall cable installation or ceiling-mounted cable installation.



SOUND ABSORPTION

Sabins per Baffle

125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	Ave.
1.0	5.4	10.8	16.3	18.7	24.0	12.7

