

AlphaSorb[®] Paintable Acoustic Panel

TECHNICAL CHARACTERISTICS

SIZE: Up to 4' x 10'

THICKNESS: 1", 2"

DENSITY: 6-7 lb. / cu. f.t fiberglass board

FINISH: Paintable Fabric

EDGE DETAIL: Square, Chemically Hardened Edge

MOUNTING: Impaling clips, Z-clips, Rotofast, or as specified

FIRE RATING: Class 1 or A per ASTM E84

NRC: 0.75 (1"), 1.00 (2")



DESCRIPTION

Our AlphaSorb[®] Paintable Acoustic Panel provides a blank canvas in a finish similar to drywall ready to accept any number of paint colors for endless design possibilities. This paintable panel is the best choice for projects requiring a soft white appearance or need to be a specific color.

Constructed with a high density fiberglass core and a high impact facing, these panels offer excellent acoustical performance. Paintable panels are available in sizes or shapes up to four foot by ten foot and may be installed as white panels or be painted on location in any color you desire.

SOUND ABSORPTION							
Thickness	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
1"	0.01	0.24	0.71	0.99	1.06	1.05	0.75
2"	0.30	0.85	1.09	1.05	0.99	1.01	1.00

