

2420 Grenoble Road Richmond, VA 23294 Toll Free: 800-782-5742



ALPHASORB® FOAM BASS TRAP TECHNICAL DATA SHEET



TECHNICAL CHARACTERISTICS

S

24" or 48" height
Open-cell melamine based foam
0.56 +/- 0.09 lb/ft ³ (Grey) 0.47 +/- 0.13 lb/ft ³ (White)
Natural Grey, Natural White
Flat or Convoluted
-40 deg F to 350 deg F

FIRE RATING: Class 1 or A per ASTM E 84

DESCRIPTION

Our AlphaSorb® Foam Bass Trap is built to provide maximum broadband absorption and low frequency control for critical listening environments. Choose from either a flat or convoluted pattern and 2' or 4' heights for maximum design versatility.

The AlphaSorb® Foam Bass Traps utilized a Class 1 fire-rated acoustical foam for use in both public and private spaces. The lightweight, wedge-shaped construction of the bass trap allows for easy corner mounting, either vertically or horizontally. These acoustic bass trap can simply rest on the floor in the corners, or you can adhere the trap with water-based foam construction adhesive.



SOUND ABSORBING PERFORMANCE (TYPE J MOUNT)									
Pattern	63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC	
Flat	0.27	0.86	1.91	1.81	1.45	1.24	1.08	1.60	
Convoluted	0.18	0.61	1.35	1.26	0.98	0.84	0.74	1.10	