

ISOLATION CUP MOUNT TECHNICAL DATA SHEET



DESCRIPTION

The Isolation Cup Mount is a high-grade neoprene isolation medium that will efficiently and economically reduce structure-borne noise and resonant vibration. These isolation mounts are made to create a buffer between noisy machinery and floors.

These mounts provide a simple attachment method for machinery on casters up to a 3" diameter or square legs up to 1" square. Isolation Cup Mounts are available in weight capacities up to 225 lbs., 175–400 lbs., or 300–625 lbs per mount. The mounts are 1-1/2" high with a 3-3/8" outside and a 2-1/4" inside diameter.

TECHNICAL CHARACTERISTICS

SIZE: 1-1/2" high
3-3/8" outer diameter
2-1/4" interior diameter

CONSTRUCTION: Neoprene covered steel cup

UNIT WEIGHT: 0.6 lbs

WEIGHT CAPACITY: up to 225 lbs. (40 Durometer)
175–400 lbs. (50 Durometer)
300–625 lbs. (60 Durometer)

MAXIMUM RATED DEFLECTION: 0.20 in.

FEATURES

- Reduces structure borne noise and vibration
- Simple attachment
- Compatible with casters up to 3" diameter
- Compatible with square legs up to 1" square

