

2420 Grenoble Road Richmond, VA 23294 Toll Free: 800-782-5742









PRIVACYSHIELD® ABSORPTIVE SOUNDPROOFING BLANKET PARTITION DATA SHEET



TECHNICAL CHARACTERISTICS

SIZE: 54" x 98.5"

THICKNESS: 1", 2" (actual size may vary

after quilt)

CONTRUCTION: Barrier backed guilted sound

> blanket that mounts to a tubular steel frame with zip ties to create

a portable acoustic screen

COLOR: Grey quilt & barrier, Black frame

Class A per ASTM E84 FIRE RATING:

NRC: 0.70 (1"), 0.85 (2")

27 (1"), 32 (2") STC:

DESCRIPTION

Our PrivacyShield® Absorptive Soundproofing Blanket Partition (formerly ABBC-13 Portable Screen) is a quilted sound barrier blanket that attaches to tubular steel frame for use as a sound partition. They may be used individually or in groups to create partial noise barriers enclosures around noisy machinery or other equipment. The quilted absorptive face helps to reduce ambient noise, while the barrier back helps to block the direct path of sound. The collapsible frame is available with or without casters for maximum portability and flexibility.

Typical uses include sound partitions for noisy areas where abuse resistance, excellent durability and portability is desired. These are the perfect material to create acoustical partitions for saws, grinders, motors, compressors and other noisy equipment.

Blanket Panel: 54" wide 1 pound per square foot barrier backed composite panel with 48" wide quilted vinyl coated cloth face. Curtain panels are manufactured with grommets for attaching to the metal frame and mating hook and loop fasteners sewn onto vertical edges.

Frame: 1" diameter powder coated tubular steel frame 48" (w) x 96" (h) with 4" high platform feet for and overall height of 100". With casters, overall

height is 103".

Casters: Optional 2" Rubber swivel casters

	SOUND ABSORPTION (ASTM C 423)												
TI	hickness	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC					
	1"	0.12	0.47	0.85	0.84	0.64	0.62	0.70					
	2"	0.07	0.27	0.96	1.13	1.08	0.99	0.85					

	SOUND TRANSMISSION LOSS (ASTM E90 & E413)												
Thickness	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	STC						
1"	11	16	24	30	35	35	27						
2"	13	20	29	40	50	55	32						

