

2420 Grenoble Road Richmond, VA 23294 Toll Free: 800-782-5742







ALPHASORB® DESIGNER PREMIUM ACOUSTIC FELT WALL PANELS DATA SHEET





TECHNICAL CHARACTERISTICS

SIZES: 10.5" x 10.5" | 21" x 10.5" | 21" x 21"

42" x 21" | 42" x 42"

THICKNESS: 27mm, 36mm

MATERIALS: 100% Polyethylene Terephthalate (PET)

55% Recycled content

WEIGHT: 27mm: 0.30 lbs. / sq. ft.

36mm: 0.41 lbs. / sq. ft.

FIRE RATING: Class A per ASTM E84

DESCRIPTION

AlphaSorb® Designer Premium Acoustic Felt Wall Panels come in various sizes and shapes to allow you to personalize your design. These panels have a patent-pending secret access compartment in the front that allows for easy and accurate installation.

FEATURES

- Quick and Easy Installation with Hidden Access Panel
- Acoustical Felt
- Core designed with Air Cavity for Maximum Sound Absorption
- Choice of 34 Colors
- Multiple Size Configurations

ENVIRONMENTAL FACTORS

- 100% Recyclable
- Low VOC Emissions
- LEED MRc4

ACOUSTICAL DATA

Tested as Type "A" Mounting

SOUND ABSORPTION (NRC)							
Thickness	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
27mm	.06	.12	.28	.61	.91	.99	.50

