

2420 Grenoble Road Richmond, VA 23294 Toll Free: 800-782-5742



PRIVACYSHIELD® AQFA-10DES SOUNDPROOFING BLANKET DATA SHEET



TECHNICAL INFORMATION

Size: 48" x 96" (nominal); rolls avaialble in 48" x 25'

Thickness: 2", 1.5 PCD fiberglass core (pre-sewn)

Finishes:

- Exterior-grade ACPC facing
- 12 colors available
- Stitched with TENARA® thread

Weight: 0.5# PSF

Mounting: Stainless steel grommets

Fire Rating:

- Class B Flammability Rated er ASTM E-84
- Flame Spread: 30
- Smoke Density: 250

Temperature Range:

-20º to +180º F

SOUND ABSORBING PERFORMANCE - TYPE A MOUNTING						
125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
0.13	0.84	0.92	0.65	0.45	0.30	0.70

DESCRIPTION

Our PrivacyShield[®] AQFA-10DES Designer Colors Soundproofing Blanket consists of a durable indoor/ outdoor rated facing quilted to both sides of a 2" thick fiberglass batting. Available in bound or unbound rolls, standard panels or even custom panel sizes. Add some color to your manufacturing and outdoor spaces!

INTERIOR/EXTERIOR APPLICATIONS

- Enclosing HVAC equipment, dust collectors, or similar where UV resistance is required
- Installed over fencing or on brick or masonry walls of buildings
- Lifespan of 10 years in the harshest exterior environments when properly installed

FEATURES

- Excellent acoustical performance
- Custom sizing
- Easy to install
- Durable, tear and abrasion-resistant
- Great UV and mildew resistance
- Highly water repellent
- Dimensionally stable; will not sag or stretch over time
- Lightweight